



coldend
clear solutions for glass inspection

STAINLESS STEEL SEPARATOR
SPACING • FLEXIBILITY

www.coldend.com

STAINLESS STEEL SEPARATOR

Applications

- Specially designed for the food industry
- Stability and improved handling on a variety of products, such as parallel sided beer bottles
- Controlling ware flow along a single line

Installation

- Kits are available to install on any type of conveyor, including lightweight aluminium and curved
 - Motors are supplied with cable connectors as standard
-

Ease of access for maintenance or job change:

The whole assembly is mounted on the lid. This enables the finger wheel to be changed or easily adjusted

Options

- Can be supplied with a Coldend inverter speed control, or the customer can choose their preferred supplier
 - For non-round containers a urethane wheel option is available
 - The finger wheel is compatible with AGR, Emhart and Inex separators
 - In addition to 8, 10 and 12 pockets the Coldend finger wheel has an additional 16 pocket configuration
 - Extended fingers can be supplied to improve handling on large diameter containers
-

Minimum container diameter (round ware): 25mm

Maximum container diameter (round ware): 200mm

Maximum containers per minute: 300

Installation line space required: 375mm

Motor: 220 – 415 vac 3ph 50Hz

0.18kw – Delta 1.39amps – Star 0.80amps

Coldend Supplied inverter: 200 – 220 vac 1ph input

200 – 220 vac 3ph output

Weight: 15kg

Size: 300mm long

300mm deep

200mm high (including motor gearbox)

Cold End Services Ltd

9 Brook Square
Conisbrough
Doncaster DN12 3HB
United Kingdom

Tel: +44 (0) 1709 770 499

Fax: +44 (0) 1709 866 666

Email: steve@coldend.com

Website: www.coldend.com

coldend
clear solutions for glass inspection